

IMPULSE 100 STANDARD LASER

Our Impulse lasers are specifically designed for optimal performance under whatever conditions you might encounter in the field. They are lightweight, extremely rugged, completely waterproof and versatile. Use them as a handheld unit or mount them on a tripod for added stability.

Hardware Specifications:

Typical Target Accuracy & Range	IMPULSE 100 STANDARD	
	(Imperial)	(Metric)
Accuracy (Typical)	0.1 - 0.2 ft	3 - 5 cm
Accuracy (Max)	0.5 ft	15 cm
Overhead cable / Stake	165 ft	50 m
Phone pole / Stockpile	330 ft	100 m
Tree / Tower	495 ft	150 m
Rock Face / Building	820 ft	250 m
Max Distance	1885 ft	575 m
Range Resolution	.01 ft	0.01 m
Inclination Limits	N/A	N/A
Inclination Accuracy	N/A	N/A
Weight	2.2 lbs.	1 kg
Size	6 x 2.5 x 5 in.	15.2 x 6.4 x 12.7 cm
Power Supply	(2) AA batteries (20 hours of use)	
Environment	Waterproof to IP 67 and NEMA 6	
Temperature	- 22 to + 140 F	-30 to + 60 C

*Max distances are approximate

Impulse Laser w/ 1.5 to 4 X Zoom Scope and Mounting Bracket



Key Features:

- Custom backlit LCD display
- Audible and visual indicators
- RS232 serial output for electronic data storage
- Selective range gating for positive target acquisition
- Filter system to discriminate reflective targets
- Cumulative distance capability
- Determines the distance between two in-line objects
- Integrates with GPS

Package Includes:

- Impulse laser
- Red-dot scope
- Hand strap
- (2) AA batteries
- Operator's manual
- Padded carrying case

Optional Accessories:

- 1.5 to 4 X zoom scope
- Yoke and staff
- Remote trigger data cable

Impulse Laser w/ Red-dot Scope and Hand Strap

